

# MINIMUM LAKE LEVELS STATUS ASSESSMENT FOR LAKE HAMPTON

December 2021  
ECT No. 210157-0800

Prepared for:



Suwannee River Water Management District  
9225 County Road 49  
Live Oak, FL 32060



1408 N. Westshore Boulevard, Suite 115  
Tampa, Florida 33607  
[www.ectinc.com](http://www.ectinc.com)

## Table of Contents

Background .....	1
Recommended MFLs.....	1
Status Assessment .....	2
Conclusions .....	4
References .....	4
Appendix A: Assessment of 2009 Pumping Scenario .....	A-1

## List of Tables

Table 1. Summary of Recommended Minimum Levels for Lake Hampton (from ECT 2021a). .....	1
Table 2. Comparison of Lake Stage Exceedance Percentiles for Current Pumping Scenario and Recommended Minimum Levels for Lake Hampton (All Elevations in ft NAVD88).....	3
Table 3. Comparison of Lake Stage Exceedance Percentiles for 2035 and 2040 Pumping Scenario and Recommended Minimum Levels for Lake Hampton (All Elevations in ft NAVD88).....	3
Table 4. Summary of MFLs Status Assessment at Lake Hampton Based on Estimated Upper FAS Drawdowns and Freeboard (ft). .....	4

## List of Figures

Figure 1. Stage Duration Curve of Model-Simulated Lake Stage Data Set (1960-2015) for Current Pumping Scenario and Recommended Minimum levels for Lake Hampton. ....	6
Figure 2. Stage Duration Curve of Model-Simulated Lake Stage Data Set (1960-2015) for 2035 Pumping Scenario and Recommended Minimum levels for Lake Hampton. ....	7
Figure 3. Stage Duration Curve of Model-Simulated Lake Stage Data Set (1960-2015) for 2040 Pumping Scenario and Recommended Minimum levels for Lake Hampton. ....	8

## Acronyms

F.S.	Florida Statutes
FAS	Floridan Aquifer System
ft	foot
HMLL	high minimum lake level
MFLs	minimum flows and levels
MLL	minimum lake level
NAVD88	North American Vertical Datum of 1988
NFSEG	North Florida Southeast Georgia Groundwater Model

RTF	Reference Timeframe (for Level/Flow)
SJRWMD	St Johns River Water Management District
SRWMD	Suwannee River Water Management District
SWFWMD	Southwest Florida Water Management District
TWA	task work assignment
USGS	United States Geological Survey

## Background

Under task work assignment (TWA): 19/20-061.007, Environmental Consulting and Technology, Inc. (ECT) was authorized by the Suwannee River Water Management District (SRWMD or District) to prepare this technical memorandum summarizing the status assessment of the minimum lake levels (MFLs) recommended for Lake Hampton in Bradford County, Florida as of completion of the MFL analysis. A status assessment is an evaluation of compliance of a waterbody with its specified MFL.

Florida Statutes (F.S.), Section 373.042(1), defines the minimum flow or level for a given watercourse as: “the limit at which further withdrawals would be significantly harmful to the water resources or ecology of the area”.

This document presents a comparison of the current and 20-year future projected conditions relative to the recommended MFLs for Lake Hampton developed in 2021 (ECT 2021a). “Current”, as used here, refers to the end of the hydrologic record utilized to develop the MFLs, in this case, 2015.

Subsection 373.0421(2), F.S., implicitly directs the analysis of the existing and projected water body level when an MFL is first developed or when it is revised:

If, at the time a minimum flow or minimum water level is initially established for a water body pursuant to s. 373.042 or is revised, the existing flow or water level in the water body is below, or is projected to fall within 20 years below, the applicable minimum flow or minimum water level, the department or governing board, as part of the regional water supply plan described in s. 373.709, shall concurrently adopt or modify and implement a recovery or prevention strategy.

The District will periodically re-assess the status of these MFLs in the future to account for changes in withdrawals and their effects on lake levels. This initial status assessment represents an evaluation of the current and projected lake levels relative to the MFLs from any aggregate change due to withdrawals but is not an evaluation of permit compliance.

## Recommended MFLs

The supporting information and analysis for the recommended MFLs is documented in *Minimum Recommended Lake Levels: Lake Hampton, Florida* (ECT 2021a). The recommended MFLs, composed of a high minimum lake level (HMLL) and a minimum lake level (MLL), are summarized in Table 1.

Table 1. Summary of Recommended Minimum Levels for Lake Hampton (from ECT 2021a).

Level	Elevation (ft NAVD88)	Level Description
High Minimum Lake Level (HMLL)	128.86	Elevation that lake stage is <u>required</u> to equal or exceed 10% of the time on a long-term basis.
Minimum Lake Level (MLL)	128.15	Elevation that lake stage is <u>required</u> to equal or exceed 50% of the time on a long-term basis.

ft NAVD88 = feet above North American Vertical Datum of 1988

## Status Assessment

The methodology for assessment of withdrawal impacts on Lake Hampton water levels is based on the total water use, whether the source of withdrawn water is directly from the lake or indirectly via groundwater withdrawals. Groundwater in the Floridan Aquifer System (FAS) is the source of most potable water used in northeastern Florida and southeastern Georgia (SJRWMD & SRWMD 2017). Due to the limited use of surface water in the Lake Hampton watershed, only groundwater use is evaluated to assess the effect of water use on the MFLs.

The hydrologic modeling in support of the evaluation of the Lake Hampton MFLs is documented in *Lake Hampton Water Budget Modeling – Updated to include Reference Timeframe Analysis* (ECT 2021b). The estimated change to groundwater levels due to withdrawals is determined through the application of a calibrated groundwater model using appropriately specified withdrawal stresses. The model used in this analysis is the North Florida Southeast Georgia Groundwater Model (NFSEG 1.1) (Durden *et al.* 2019). A series of reference timeframe head (RTF) adjustment factors were estimated for the groundwater levels beneath Lake Hampton for the period from 1948 through 2015.

The “no-pumping” groundwater level data set was created by adding the RTF adjustment factors to the measured groundwater level data set. The groundwater level data sets for the “current pumping” (2015) scenario and the predicted 2035 scenario were created based on the simulated upper Floridan Aquifer System (FAS) average drawdowns for 2015 and 2035 using the NFSEG model. The current pumping scenario drawdowns represent a 2015 average water use for the District and a 2011-2015 average water use for the SJRWMD portions of the model domain. The 2035 scenario drawdowns represent best available model domain-wide growth projections. Finally, a 20-year projected condition (2040) was estimated based on the predicted 2035 upper FAS drawdown with a growth factor from 2030 to 2035 projected conditions.

A long-term water budget model developed for Lake Hampton (ECT 2021b) was utilized to estimate changes to lake levels due to groundwater withdrawals for the current pumping, 2035, and 2040 scenarios. The long-term model was simulated for a total of 55.7 years from 4/25/1960 through 12/31/2015.

Based on the SWFWMD MFLs methods (SWFWMD 2020), determination of the MFL status at Lake Hampton is made through a stage duration analysis of the model-simulated lake stage data sets for the current and predicted scenarios, in comparison to the recommended MFL levels (ECT 2021a).

### Assessment of Current Pumping Scenario

Based on the simulated average upper FAS drawdowns provided by the District using the NFSEG model, the current pumping (as of 2015) upper FAS drawdown value was estimated at 5.6 feet relative to no-pumping conditions. The groundwater level data set for the current pumping scenario was developed by subtracting 5.6 feet from the no-pumping data set.

The long-term water budget model was used to simulate the current pumping scenario. The 55.7-year model-simulated lake stage data set was utilized in the assessment of the current pumping scenario. The stage duration analysis results of the model-simulated lake stage data set are presented in Table 2 and Figure 1.

Based on the SWFWMD MFLs procedures, the HMLL is required to be reached or exceeded 10% of the time over a long-term record and the MLL is required to be reached or exceeded 50% of the time. As shown in Table 2 and Figure 1, the recommended HMLL and MLL levels are both being met under the current pumping scenario.

*Table 2. Comparison of Lake Stage Exceedance Percentiles for Current Pumping Scenario and Recommended Minimum Levels for Lake Hampton (All Elevations in ft NAVD88).*

Percentile	Current Pumping Scenario	Recommended Minimum Levels
P10	129.58	128.86 (HMLL)
P50	128.84	128.15 (MLL)

Appendix A provides the MFLs status assessment results for 2009 conditions, for comparison purposes. Results for 2009 conditions were of interest because that year was used for calibration of the NFSEG model. The assessment results of the 2009 pumping scenario are similar to the current pumping scenario. Note that the groundwater level data sets between the 2009 and current pumping scenarios differ by 0.3 foot, which is approximately 8% of the mean annual fluctuation in seasonal groundwater levels.

## Assessment of Predicted 2035 and 2040 Pumping Scenarios

Based on the simulated average upper FAS drawdowns provided by the District using the NFSEG model, the predicted 2035 upper FAS drawdown value was estimated at 7.4 feet relative to no-pumping conditions. The groundwater level data set for the predicted 2035 scenario was developed by subtracting 7.4 feet from the no-pumping data set.

The upper FAS drawdown value for the 20-year projected condition (2040) was estimated at 7.7 feet relative to no-pumping conditions, based on the predicted 2035 upper FAS drawdown with a growth factor from 2030 to 2035 projected conditions for all water use categories except agriculture. Agricultural water use for 2040 was held to 2035 levels based on current best available data which indicate lower projected demands through 2045. The groundwater level data set of the predicted 2040 scenario was developed by subtracting 7.7 feet from the no-pumping data set.

The long-term water budget model was used to simulate the predicted 2035 and 2040 pumping scenarios. The stage duration analysis results of the model-simulated lake stage data sets are presented in Table 3 for the predicted 2035 and 2040 pumping scenarios and illustrated on Figures 2 and 3 for the 2035 and 2040 pumping scenarios, respectively. Based on the stage duration analysis results (Table 3 and Figures 2 and 3), the recommended HMLL and MLL levels would be met under the predicted 2035 and 2040 pumping scenarios.

*Table 3. Comparison of Lake Stage Exceedance Percentiles for 2035 and 2040 Pumping Scenario and Recommended Minimum Levels for Lake Hampton (All Elevations in ft NAVD88).*

Percentile	2035 Pumping Scenario	2040 Pumping Scenario	Recommended Minimum Levels
P10	129.55	129.55	128.86 (HMLL)
P50	128.80	128.79	128.15 (MLL)

## Conclusions

To summarize the MFLs status for the current and predicted scenarios evaluated, the stage duration analysis results were used to determine the amount of water available for withdrawal (freeboard) (Table 4). Freeboard is defined as an upper FAS drawdown (feet) that is allowable before a MFL is no longer achieved. The freeboard for each MFL metric is determined by increasing or decreasing the upper FAS drawdown, running the long-term water budget iteratively after changing the upper FAS levels, and replotting the lake level frequency analysis results until the MFL is just met. The stage duration analysis results and the upper FAS freeboard for each of the recommended MFLs are documented in *Lake Hampton Water Budget Modeling – Updated to include Reference Timeframe Analysis* (ECT 2021b). Based on the status assessment results, Lake Hampton water levels meet the MFLs for the current pumping (2015 conditions) and predicted 2035 and 2040 pumping scenarios (Figures 1 through 3 and Tables 2 and 3).

As noted above, Section 373.0421, F.S., directs the assessment of a water body when an MFL is first developed or when it is revised. If the existing flow or water level in the water body is below or projected to fall below the MFL within 20 years, the department (FDEP) or governing board (water management district) is directed to “concurrently adopt or modify and implement a recovery or prevention strategy”. Based on the assessment results listed in Table 4, a Prevention or Recovery Strategy is not required to be developed for Lake Hampton.

*Table 4. Summary of MFLs Status Assessment at Lake Hampton Based on Estimated Upper FAS Drawdowns and Freeboard (ft).*

	High Minimum Lake Level (HMLL)	Minimum Lake Level (MLL)
“No-pumping” Conditions – Freeboard	49.3	23.5
“Current” Conditions – 2015 Drawdown	5.6	5.6
“Current” Conditions – 2015 Freeboard	43.7	17.9
“Projected” Conditions – 2035 Drawdown	7.4	7.4
“Projected” Conditions – 2035 Freeboard	41.9	16.1
“Projected” Conditions – 2040 Drawdown	7.7	7.7
“Projected” Conditions – 2040 Freeboard	41.6	15.8
Status	Meeting	Meeting

## References

Durden, D., Gordu F., Hearn D., Cera T., Desmarais T., Meridith L., Angel A., Leahy C., Oseguera J. and Grubbs T. 2019. North Florida Southeast Georgia Groundwater Model (NFSEG v1.1). St. Johns River Water Management District Technical Publication SJ2019-01. Palatka, Fla. St. Johns River Water Management District. 513 pp.

(ECT) Environmental Consulting and Technology, Inc. 2021a. Minimum Recommended Lake Levels: Lake Hampton, Florida. Prepared for Suwannee River Water Management District. Environmental Consulting & Technology, Inc., Tampa, Florida.

ECT. 2021b. Lake Hampton Water Budget Modeling – Updated to Include Reference Timeframe Analysis. Prepared for Suwannee River Water Management District. Environmental Consulting & Technology, Inc., Tampa, Florida.

(SJRWMD and SRWMD) St. Johns River Water Management District and Suwannee River Water Management District. 2017. North Florida Regional Water Supply Plan (2015 – 2035). St. Johns River Water Management District, Palatka, Florida and Suwannee River Water Management District, Live Oak, Florida.

(SWFWMD) Southwest Florida Water Management District. 2020. Revised Minimum and Guidance Levels Based on Reevaluation of Adopted Levels for Lake Marion in Levy County, Florida. Resource Evaluation Section, Water Resources Bureau. Brooksville, Florida.






Figure 1. Stage Duration Curve of Model-Simulated Lake Stage Data Set (1960-2015) for Current Pumping Scenario and Recommended Minimum levels for Lake Hampton.




Figure 2. Stage Duration Curve of Model-Simulated Lake Stage Data Set (1960-2015) for 2035 Pumping Scenario and Recommended Minimum levels for Lake Hampton.




Figure 3. Stage Duration Curve of Model-Simulated Lake Stage Data Set (1960-2015) for 2040 Pumping Scenario and Recommended Minimum levels for Lake Hampton.

## Appendix A: Assessment of 2009 Pumping Scenario

Using the same methodology described in this technical memo, the groundwater level data set can be developed for 2009 conditions. The drawdown of 5.9 feet for 2009 was subtracted from the no-pumping data set to generate the groundwater level data set for the 2009 pumping scenario at Lake Hampton. Note that the groundwater level data set for the 2009 pumping scenario is approximately 0.3 foot lower than the current pumping (2015) data set, i.e., water use in 2015 is less than the 2009 conditions.

The long-term water budget model was used to simulate the 2009 pumping scenario. The stage duration analysis results of the model-simulated lake stage data set are presented in Table A-1 and Figure A-1. As shown in Table A-1 and Figure A-1, the recommended HMLL and MLL levels would be met under the 2009 pumping scenario, based on the SWFWMD MFLs methods.

*Table A-1. Comparison of Lake Stage Exceedance Percentiles for 2009 Pumping Scenario and Recommended Minimum Levels for Lake Hampton (All elevations in ft NAVD88).*

Percentile	Current Pumping Scenario	Recommended Minimum Levels
P10	129.58	128.86 (HMLL)
P50	128.83	128.15 (MLL)




Figure A-1. Stage Duration Curve of Model-Simulated Lake Stage Data Set (1960-2015) for 2009 Pumping Scenario and Recommended Minimum levels for Lake Hampton.